

LINKS BROADCAST

An SCC International Broadcast Facility
Satellite Broadcast Services

Links 4 specification



This 1.5m C/Ku-band HD/SD flydrive system is a compact lightweight system designed for rapid deployment. The antenna can be used either as a traditional flyaway or vehicle-mounted system to support in-country travel and rapid deployment.

IATA Weight Compliant

Antenna Advent 1.5m Lightweight fully motorized flydrive

System C/Ku Band

HPA 2 x 400 Watt Xicom with full redundancy switching

SD Encoders 2 x DVE5000 lightweight powerful encoders with 4:2:2 & BISS

HD Encoders 2 x Tandberg 5788 HD Encoders 4:2:0/4:2:2 with RAS, BISS, 8PSK, DVBS2, 8 Audio Channel Upgrade

HD IRD Tandberg 1290 HD/SD 4:2:0/4:2:2 with RAS, BISS, 8PSK, DVBS2, 8 Audio Channel Upgrade

SD IRD Tandberg 1260 4:2:0/4:2:2 with RAS, BISS, 8PSK

Audio Monitoring Wohler System with Dolby 5.1 Monitoring

Vision Monitoring 2 x 7" HD/SD Monitors, HD SDI Inputs

AV Switching Matrix switching system

IFB Comms 2 Channel GSM system for IFB & talkback

Bookings +44 (0)1992 822750

Email bookings@linksbroadcast.com

www.linksbroadcast.com

Links Broadcast, Fieldings Road, Cheshunt, Herts EN8 9TL, UK